

MC2

802.11a/b/g/n WLAN Ethernet & Serial Adapter

Description:

The MC2 provides network connections between devices equipped with Ethernet ports or serial interfaces and wireless LAN networks. The typical usage area for the MC2 is the broad field of industrial WLAN applications in machine-to-machine communication. This includes mobile installations such as forklifts or AGV's.



MC2-SL



MC2-SL-M12



MC2-SC

Properties:

Hardware:

- Processor board with ARM® Cortex®-A9 Core
- Memory: 128MByte DDR-RAM and 4GB Flash
- 802.11a/b/g/n for 2.4 + 5 GHz WLAN, Data rate up to 300 MBit/s
- 2 x Gigabit LAN interface
- 1 x RS232 or RS485 or RS422 serial interface
- 1 x USB2 Port also for interface extensions
- 1 x relay switch
- 1 x aux input
- Power supply 10-72V or 802.3af PoE via LAN Port 1
- Robust aluminum housing with various mounting options
- Largely mechanical and functional compatibility to the earlier models WLX + ESCG.

Functions:

- Configuration via the website or by using the MC-Config program.
- Different bridge modes to connect the LAN clients.
- NAT
- Single Client NAT
- Single Client Cloning
- Level 2 Bridge
- MWLC Mode
- Certificate management for authentication via 802.1x
- SCEP (Simple Certificate Enrollment Protocol)
- Fast-Roaming 802.11r
- Serial-Client via TCP or UDP

Device Options:

Mounting:

- 1) side mounting brackets (MC2-SL...)
- 2) DIN rail mounting clip (MC2-SC...)

Power supply connection:

- 1) 5 pol. M12 connector (incl Relay) (MC2-Sx-M12)
- 2) 8pol terminal block (Weidmüller) (incl. Relay + Aux. input)
- 3) 3pol M8 connector (Power supply) (MC2-Sx-M8)
 - optional 4pol M8 for Relay + Aux. input (MC2-Sx-M8-REL)

Antenna connector:

- 1) 2 x RP-SMA (standard)
- 2) 1 or 2 TNC or RPTNC

Serial Interface:

- 1) 1 x RS232 (Standard)
- 2) 1 x RS485 (RS422)

Technical data:

Specification:	
<i>Ethernet</i>	2 x 10/100/1000 MBit Auto MDI/MDIX
<i>Serial</i>	1 x RS232, 300-460,8 KBit/s, RTS, CTS, DSR, DTR or RS485
<i>USB</i>	1 x USB 2.0 to connect printers or USB adapter with various other interfaces
<i>Relay</i>	1 x change-over switch max 1A@24V, max 125VAC
<i>AUX-Input</i>	1 x galv. isolated 10 – 72V
<i>Antenna connectors</i>	2 x RPSMA (optional TNC or RPTNC)
<i>Power supply</i>	10 – 72VDC or 802.3af PoE via the LAN Port
<i>Energy consumption</i>	<= 5W (3W typical)
<i>Operating temperature range</i>	0-60°
<i>Dimensions</i>	105x125x35mm
<i>Weight</i>	ca. 400g

WLAN-Interface:		
<i>Technologies</i>	802.11 a/b/g/n WLAN (2.4 + 5 GHz Band)	
<i>Antennas:</i>	2 Antennas (2T2R MIMO) up to 300 Mbit /s	
<i>Encoding</i>	WEP (64,128bit) + TKIP/AES	
<i>Security</i>	802.11i WPA(2) – PSK 802.1x EAP-PEAP, -TLS, -TTLS, -LEAP	
<i>Channels</i>	802.11b/g/n ETSI 1-13, USA/Canada 1-11 802.11a/n ETSI 19, USA/Canada 12	
<i>Data rates</i>	<i>Mode</i>	<i>Data rate</i>
	802.11b:	1, 2, 5.5, 11Mbps
	802.11g / a	6, 9, 12, 18, 24, 36, 48, 54Mbps
	802.11n (20MHz)	1Nss: max. 72.2Mbps 2Nss: max. 144.4Mbps
	802.11n (40MHz)	1Nss: max. 150Mbps 2Nss: max. 300Mbps
<i>Transmit power</i>	802.11b/g 17 dBm	802.11a 15 dBm
	802.11gn 16 dBm	802.11an 15 dBm

Order codes:

	Option	Order code
Housing		
	Housing with mounting brackets	MC2-SL....
	Housing with DIN-rail-clip	MC2-SC....
Power supply connection		
	M12 connector	MC2-Sx-M12
	8pol. Weidmüller terminal block	MC2-Sx-WK8
	M8 connector	MC2-Sx-M8
IO-Option		
	Relay	MC2-Sx-xx-REL
	Aux-Input	MC2-Sx-xx-INP
Serial	Standard: 1 x RS232	
	1 x RS422	MC2-Sx-xx-RS422
	1 x RS485	MC2-Sx-xx--RS485
Antenna Options	Standard: 2 x RPSMA	
	1 or 2 TNC Antenna connector(s)	MC2-Sx-xx-1(2)TNC
	1 or 2 RPTNC Antenna connector(s)	MC2-Sx-xx-1(2)RTNC